



## Latex Modifier

### DESCRIPTION:

GemSeal® Latex Modifier II is a blended co-polymer, designed to modify coal tar emulsion based pavement sealers.

### FEATURES:

- Greater tensile strength and durability
- Faster drying and curing.
- Increased resistance to scuffing and power steering marks
- Vastly improved aggregate bonding
- Ability to substantially increase amounts of aggregate loading
- Additional oil, water and ultraviolet light resistance
- Deeper black color

### PACKAGING:

Available in 5 gallon pails and 55 gallon drums.

### STORAGE:

Store in a cool, dry area. Avoid freezing. Product is no longer useful after freezing.

### CLEAN-UP:

Spillage may be easily removed with water if still wet.

### SERVICE:

Timely service is available within a 300 mile radius of our manufacturing facilities.

### ATTENTION:

GemSeal® Latex Modifier II should be protected from freezing.

### CAUTION:

Keep out of reach of children. In case of contact with eyes, immediately flush with large quantities of water and contact a physician. For skin contact, flush with large amounts of water, contact a physician if irritation develops. If swallowed DO NOT induce vomiting. If conscious, give several glasses of water and immediately contact a physician. Do not give any unconscious person anything by mouth.

### USES:

Increases durability of finished coating. For situations demanding faster drying characteristics with additional viscosity and strength needed to suspend and bond low to high levels of aggregate.

### COMPOSITION:

GemSeal Latex Modifier II is a blended product based on acrylonitrile and other cross linking polymers that modify viscosity, improve mix rheology, and enhance leveling and water resistance.

### SPECIFICATIONS:

Federal Aviation Administration Engineering Brief No 46A.

### FORMULATIONS:

Numerous design mixes are available to meet varied job-site paving conditions. Typical design recommends addition of 2 to 5 gallons per 100 gallons of GemSeal Pavement Sealer Concentrate.



# Latex Modifier

## MANUFACTURING & CUSTOMER SERVICE

Atlanta, GA 404-696-7660 404-691-9049 - Fax	Boston, MA 508-791-6366 508-791-6339 - Fax	Dallas, TX 214-333-4343 214-333-4399 - Fax	Greensboro, NC 336-854-8200 336-854-8202 - Fax	Tampa, FL 813-623-3941 813-626-4103 - Fax
Baltimore, MD 410-238-3413 410-238-3414 - Fax	Chicago, IL 847-678-6220 847-678-2652 - Fax	Detroit, MI 734-753-4413 734-753-9033 - Fax	Memphis, TN 901-775-2585 901-755-2590 - Fax	



Corporate Headquarters:  
8201 Arrowridge Blvd. Charlotte, NC 28273

LIMITED 1 YEAR PRODUCT WARRANTY FROM DATE OF MANUFACTURE: Bonsal American warrants that this product and the materials used therein meet or exceed the applicable standards listed and enforced at the time of manufacture. Bonsal American will replace any product or part which proves defective due to quality of ingredients used or due to the manufacturing process itself. This Warranty shall apply only if the product is used in strict accordance with applicable specifications and instructions provided by Bonsal American for its use, and Bonsal American shall not be liable otherwise. Replacement of any defective product, or, at Bonsal American option, refund of the purchase of any defective product shall be the buyer's sole remedy under this Warranty, and Bonsal American shall in no event be liable for any damages in excess of the purchase price of the defective product. BONSAL AMERICAN SHALL IN NO EVENT BE LIABLE FOR ANY CONSEQUENTIAL, INCIDENTAL, OR SPECIAL DAMAGES.

This Warranty constitutes the sole warranty given by Bonsal American in connection with this product, and Bonsal American has authorized no person to make or give any other warranties or representation, oral or written on its behalf. IN PARTICULAR, THERE ARE NO IMPLIED WARRANTIES, INCLUDING WITHOUT EXCEPTION WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. No modification of this Warranty in favor of any buyer shall be valid unless given in writing and signed by an officer of Bonsal American.