

The Pro's Choice Since 1936

SAKRETE®

All Weather Blacktop Patch

Sakrete® All Weather Blacktop Patch is a high performance patching material containing a mixture of blended asphalts, aggregates and special additives. For repairing potholes in blacktop drives, walls and parking lots, in any temperature, wet or dry conditions, for permanent pothole repairs. Do not use SAKRETE® All Weather Blacktop Patch as a curb, speed bump, ramp or for driveway extensions. Maximum repair area is not to exceed 3 feet by 3 feet by 4 inches.

SAFETY:

READ and UNDERSTAND the Material Safety Data Sheet (MSDS) before using this product. WARNING: Wear protective clothing and equipment. For emergency information, call CHEMTREC at 800-424-9300 or 703-527-3887 (outside USA). KEEP OUT OF REACH OF CHILDREN.

PREPARATION:

Chisel out loose blacktop. Square up area to be patched ensuring that the sides are vertical. Avoid a birdbath shaped hole. Clean area to be patched. Remove all loose particles, dirt, grass, etc. If sub-base is unsound, remove the unsound portion of the sub-base and replace with clean compacted gravel or stone.

PLACEMENT & COMPACTION:

Pour a 2 inch layer of loose SAKRETE® All Weather Blacktop Patch into the area to be patched, Level the loose material and then compact to a 1 inch layer. Compact with a tamper or a 4 inch x 4 inch post. PLACE AND COMPACT additional layers until desired thickness is achieved. Riding over the patch with a car will not provide sufficient compaction. Compaction must be sufficient to cause the stone in the blacktop to lock together and minimize voids in each layer. If the blacktop is not completely compacted, the patch will remain soft and the material may not stay in place. Properly compacted SAKRETE® All Weather Blacktop Patch will continue to harden over time.

TIPS FOR USE:

SAKRETE® All Weather Blacktop Patch may be opened to traffic immediately after being thoroughly compacted. Under certain conditions the surface may remain tacky for a short period of time. If this occurs, a light layer of sand may be helpful. Do not apply driveway sealer to the patched area for a period of 60-90 days of warm weather.

STORAGE:

STORAGE: If stored in an airtight container, unused material may be usable up to six months later. In general, if the material can be easily removed from the container and there are no lumps, it may be suitable for use.

COVERAGE:

How Much All Weather Blacktop Patch Do I Need (60 lb. bags) <small>(Estimate of the number of whole 60 lb. (27.2 kg) bags of SAKRETE® All Weather Blacktop Patch required to make the following repairs.)</small>					
Area in Sq. Ft. (sq m)	3 (0.3)	4 (0.4)	5 (0.5)	6 (0.6)	
1" Deep (25 mm)	1	1	2	2	BAGS
2" Deep (50 mm)	2	2	3	3	BAGS
3" Deep (75 mm)	2	3	4	4	BAGS
4" Deep (100 mm)	3	4	5	5	BAGS

How Much All Weather Blacktop Patch Do I Need (25 lb. buckets)					
Area in Sq. Ft. (sq m)	3 (0.3)	4 (0.4)	5 (0.5)	6 (0.6)	
1" Deep (25 mm)	2	2	3	3	BUCKETS
2" Deep (50 mm)	3	4	5	6	BUCKETS
3" Deep (75 mm)	5	6	8	9	BUCKETS
4" Deep (100 mm)	6	8	10	12	BUCKETS

To determine coverage calculate the following:
length x width x depth (all in feet) = cubic feet

YIELD:

25 lbs. (11.3 kg) .17 cu. ft. (.005 cu. m)
60 lbs. (27.2 kg) .4 cu. ft. (.01 cu. m)

PACKAGING:

25 lbs. (11.3 kg) UPC: 7-64661-16125-7
60 lbs. (27.2 kg) UPC: 7-64661-16060-1

The Pro's Choice Since 1936

SAKRETE®

All Weather Blacktop Patch

WARNING! Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Exposure may result in irritation of the skin. **FIRST AID:** In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get prompt medical attention; for skin, wash thoroughly with plenty of soap and water.

LIMITED PRODUCT WARRANTY

The manufacturer warrants that this product shall be of merchantable quality when used or applied in accordance with the manufacturer's instructions. This product is not warranted as suitable for any purpose other than the general purpose for which it is intended. This warranty runs for one (1) year from the date the product is purchased. ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ON THIS PRODUCT IS LIMITED TO THE DURATION OF THIS WARRANTY. Liability under this warranty is limited to replacement of defective product or, at the manufacturer's option, refund of the purchase price. CONSEQUENTIAL AND INCIDENTAL DAMAGES ARE NOT RECOVERABLE UNDER THIS WARRANTY.

The SAKRETE Companies
866-SAKRETE
866-725-7383
www.sakrete.com

REV 3-09