



Tar Prime

DESCRIPTION:

GemSeal® Tar Prime is a unique ready to use, job-proven primer formulation of acrylic polymers that allows sealer materials to bond effectively and dry quickly.

USES:

Prevents oil and grease spots from “bleeding” through fresh blacktop sealer. Also for priming of grease, oil and gasoline concentration on asphaltic concrete surfaces before application of sealcoat materials.

APPLICATION:

1. Clean spots thoroughly with water.
2. Scrape heavy spots and remove loose materials. Particularly resistant spots may need cleaning with a strong detergent or driveway cleaner.
3. Stir Tar Prime until thoroughly mixed.
4. Apply to area with clean brush, broom or spray. Do not dilute.
5. Allow to dry to touch before applying sealer over primer (usually two hours or less).

WEATHER CONDITIONS:

Apply only when air and ground temperature is 50°F and rising. Do not apply if rain is expected within four hours.

CLEAN-UP:

Clean application tools at once with soap and water.

COVERAGE:

Coverage varies between 250 and 300 square feet per gallon depending upon surface texture and porosity of area coated.

PACKAGING:

Available in 5 gallon pails.

STORAGE:

Keep from freezing. Do not store in direct sunlight. Do not store where temperature exceeds 100°F.

SERVICE:

Timely service is available within a 300 mile radius of our manufacturing facilities.

ATTENTION:

GemSeal® Tar Prime should be protected from freezing.

CAUTION:

Keep out of reach of children. In case of contact with eyes, immediately flush with large quantities of water and contact a physician. For skin contact, flush with large amounts of water, contact a physician if irritation develops. If swallowed DO NOT induce vomiting. If conscious, give several glasses of water and immediately contact a physician. Do not give any unconscious person anything by mouth.



Tar Prime

MANUFACTURING & CUSTOMER SERVICE

Atlanta, GA 404-696-7660 404-691-9049 - Fax	Boston, MA 508-791-6366 508-791-6339 - Fax	Dallas, TX 214-333-4343 214-333-4399 - Fax	Greensboro, NC 336-854-8200 336-854-8202 - Fax	Tampa, FL 813-623-3941 813-626-4103 - Fax
Baltimore, MD 410-238-3413 410-238-3414 - Fax	Chicago, IL 847-678-6220 847-678-2652 - Fax	Detroit, MI 734-753-4413 734-753-9033 - Fax	Memphis, TN 901-775-2585 901-755-2590 - Fax	



Corporate Headquarters:
8201 Arrowridge Blvd. Charlotte, NC 28273

LIMITED 1 YEAR PRODUCT WARRANTY FROM DATE OF MANUFACTURE: Bonsal American warrants that this product and the materials used therein meet or exceed the applicable standards listed and enforced at the time of manufacture. Bonsal American will replace any product or part which proves defective due to quality of ingredients used or due to the manufacturing process itself. This Warranty shall apply only if the product is used in strict accordance with applicable specifications and instructions provided by Bonsal American for its use, and Bonsal American shall not be liable otherwise. Replacement of any defective product, or, at Bonsal American option, refund of the purchase of any defective product shall be the buyer's sole remedy under this Warranty, and Bonsal American shall in no event be liable for any damages in excess of the purchase price of the defective product. BONSAL AMERICAN SHALL IN NO EVENT BE LIABLE FOR ANY CONSEQUENTIAL, INCIDENTAL, OR SPECIAL DAMAGES.

This Warranty constitutes the sole warranty given by Bonsal American in connection with this product, and Bonsal American has authorized no person to make or give any other warranties or representation, oral or written on its behalf. IN PARTICULAR, THERE ARE NO IMPLIED WARRANTIES, INCLUDING WITHOUT EXCEPTION WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. No modification of this Warranty in favor of any buyer shall be valid unless given in writing and signed by an officer of Bonsal American.