



## TARLOC® MPC PRIMER Primer for Coal Tar Emulsion Sealer

### DESCRIPTION:

Tarloc® MPC Primer is a pavement primer for oxidized, worn difficult to clean surfaces to improve bonding and wear of coal tar emulsion sealcoats.

### FEATURES:

- Primer for badly oxidized asphalt pavements prior to sealing
- Primer for hard to clean areas, and polished aggregate conditions.
- Primer for concrete pavements prior to sealing.
- Oil spot sealer on both asphalt and concrete.
- Black-out paint for traffic/parking lines, etc.

### APPLICATION:

Tarloc® MPC can be applied by brush, squeegee, line paint sprayer or bulk truck spray-bar/hand wand. Since mild settling is possible, the product should be thoroughly stirred before application to the pavement. Stir to a uniform consistency. Apply Tarloc MPC in a thin film. Avoid over application. A wearing coat (s) of Latex modified sealer is then recommended over the Tarloc MPC Primer.

### APPLICATION RATE:

.025 to .050 gal./sq. yd.

### For Asphalt Surfaces:

Mix 1 part Tarloc MPC with 1 part water.

### For Concrete Surfaces:

Mix 1 part Tarloc MPC to 2 parts water.

### PHYSICAL PROPERTIES:

APPEARANCE Viscous, grey-green liquid

SOLIDS 30%

VISCOSITY 2,000 cPs

DENSITY 9.0 Lb./Gal.

ODOR Coal Tar

DRIED FILM COLOR Black

DRYING TIME 10 to 30 minutes (depending on surface conditions and thickness of application).

### PACKAGING:

Available in 5 gallon pails.

### STORAGE:

Store in a cool, dry area. Avoid freezing. Product is no longer useful after freezing.

### SPECIAL HANDLING:

Tarloc® MPC is slightly more irritable to the skin than regular pavement sealer. Protective clothing and skin creams should be used at all times.

### CAUTION:

Contains coal tar, a skin irritant. Keep out of reach of children. Do not take internally. Avoid prolonged or repeated contact with skin or breathing of vapors. In case of contact with eyes, flush with plenty of water, and seek immediate medical attention. Use with adequate ventilation. Do not use in confined areas.

Tarloc® is the registered trademark of Southern Emulsions, Inc.



# Tarloc MPC Primer

## CUSTOMER SERVICE

Atlanta, GA 404-696-7660 404-691-9049 - Fax	Boston, MA 508-791-6366 508-791-6339 - Fax	Dallas, TX 214-333-4343 214-333-4399 - Fax	Greensboro, NC 336-854-8200 336-854-8202 - Fax	Tampa, FL 813-623-3941 813-626-4103 - Fax
Baltimore, MD 410-238-3413 410-238-3414 - Fax	Chicago, IL 847-678-6220 847-678-2652 - Fax	Detroit, MI 734-753-4413 734-753-9033 - Fax	Memphis, TN 901-775-2585 901-755-2590 - Fax	



Corporate Headquarters:  
8201 Arrowridge Blvd. Charlotte, NC 28273

LIMITED 1 YEAR PRODUCT WARRANTY FROM DATE OF MANUFACTURE: Bonsal American warrants that this product and the materials used therein meet or exceed the applicable standards listed and enforced at the time of manufacture. Bonsal American will replace any product or part which proves defective due to quality of ingredients used or due to the manufacturing process itself. This Warranty shall apply only if the product is used in strict accordance with applicable specifications and instructions provided by Bonsal American for its use, and Bonsal American shall not be liable otherwise. Replacement of any defective product, or, at Bonsal American option, refund of the purchase of any defective product shall be the buyer's sole remedy under this Warranty, and Bonsal American shall in no event be liable for any damages in excess of the purchase price of the defective product. BONSAL AMERICAN SHALL IN NO EVENT BE LIABLE FOR ANY CONSEQUENTIAL, INCIDENTAL, OR SPECIAL DAMAGES.

This Warranty constitutes the sole warranty given by Bonsal American in connection with this product, and Bonsal American has authorized no person to make or give any other warranties or representation, oral or written on its behalf. IN PARTICULAR, THERE ARE NO IMPLIED WARRANTIES, INCLUDING WITHOUT EXCEPTION WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. No modification of this Warranty in favor of any buyer shall be valid unless given in writing and signed by an officer of Bonsal American.