



Tack Coat (Asphalt Emulsion Type SS-1)

DESCRIPTION:

GemSeal® Tack Coat asphaltic emulsion serves as a tack coat for better coating adhesion on asphalt pavement surfaces.

USES:

Bonding agent between new bituminous asphalt and old.

PREPARATION:

Clean surface of all loose materials, dirt and dust.

MIXING:

Mix well to a uniform consistency.

SPREADING:

May be applied by spray, brush or squeegee.

DO NOT DILUTE

WEATHER CONDITIONS:

Apply only when air and ground temperature is 50°F and rising. Do not apply if rain is expected within eight hours.

COLOR:

Black (when dry)

COVERAGE:

Material covers approximately 20 square yards per gallon.

CLEAN-UP:

Clean tools with water immediately after use. Filler remaining on tools may be removed with mineral spirits.

PACKAGING:

Available in 5 gallon pails, 55 gallon drums and also available in bulk.

STORAGE:

Keep from freezing. Do not store in direct sunlight. Do not store where temperature exceeds 100°F.

SERVICE:

Timely service is available within a 300 mile radius of our manufacturing facilities.

CAUTION:

HARMFUL IF SWALLOWED. Contact with any part of the body may cause skin irritation. Wash off with water immediately. Wearing gloves is recommended. KEEP OUT OF THE REACH OF CHILDREN. KEEP FROM FREEZING. Contains Asphalt CAS #8052-42-4



Tack Coat SS-1

MANUFACTURING & CUSTOMER SERVICE

| | | | | |
|-------------------------------------------------------|-----------------------------------------------------|-----------------------------------------------------|--------------------------------------------------------|---------------------------------------------------|
| Atlanta, GA (866) 264-2873 404-691-9049 - Fax | Boston, MA (866) 264-2873 508-791-6339 - Fax | Dallas, TX (866) 264-2873 214-333-4399 - Fax | Greensboro, NC (866) 264-2873 336-854-8202 - Fax | Tampa, FL (866) 264-2873 813-630-1660 - Fax |
| Baltimore, MD (866) 264-2873 410-238-3414 - Fax | Chicago, IL (866) 264-2873 847-678-2652 - Fax | Detroit, MI (866) 264-2873 734-753-9033 - Fax | Memphis, TN (866) 264-2873 901-755-2590 - Fax | |

GemSeal is a registered trademark of Bonsal American, an Oldcastle Company



Bonsal American, Inc
Corporate Headquarters:
8201 Arrowridge Blvd. Charlotte, NC 28273

LIMITED 1 YEAR PRODUCT WARRANTY FROM DATE OF MANUFACTURE: Bonsal American warrants that this product and the materials used therein meet or exceed the applicable standards listed and enforced at the time of manufacture. Bonsal American will replace any product or part which proves defective due to quality of ingredients used or due to the manufacturing process itself. This Warranty shall apply only if the product is used in strict accordance with applicable specifications and instructions provided by Bonsal American for its use, and Bonsal American shall not be liable otherwise. Replacement of any defective product, or, at Bonsal American option, refund of the purchase of any defective product shall be the buyer's sole remedy under this Warranty, and Bonsal American shall in no event be liable for any damages in excess of the purchase price of the defective product. BONSAL AMERICAN SHALL IN NO EVENT BE LIABLE FOR ANY CONSEQUENTIAL, INCIDENTAL, OR SPECIAL DAMAGES.

This Warranty constitutes the sole warranty given by Bonsal American in connection with this product, and Bonsal American has authorized no person to make or give any other warranties or representation, oral or written on its behalf. IN PARTICULAR, THERE ARE NO IMPLIED WARRANTIES, INCLUDING WITHOUT EXCEPTION WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. No modification of this Warranty in favor of any buyer shall be valid unless given in writing and signed by an officer of Bonsal American.